

PRODUCT DESIGNATION	OUTSIDE DIMENSIONS		MAXIMUM OPENING WIDTH		ANCHOR HOLE DISTANCE	WEIGHT	MAXIMUM ALLOWED WATER HEIGHT	CLEARANCE REQUIRED BEHIND FRAME	NO. OF ANCHOR BOLTS	ANCHOR BOLT LOADS	
	HEIGHT	WIDTH	CONCRETE & MASONRY WALL *	MAXIMUM ALLOWABLE**						AXIAL	SHEAR
4 X 92	48"	92"	76"	86"	90.3"	140 lb	4 ft 6 ft (STACKED)	4" 6" (STACKED)	10	2000 lbs	1600 lbs
4 X 54	48"	54"	38"	48"	52.3"	100 lb	4 ft 6 ft (STACKED)	2" 4" (STACKED)	10	2000 lbs	1600 lbs
2 X 92	24"	92"	76"	86"	90.3"	74 lb	2 ft	4"	6	2000 lbs	1600 lbs
2 X 54	24"	54"	38"	48"	52.3"	52 lb	2 ft	2"	6	2000 lbs	1600 lbs

* MAXIMUM OPENING WIDTH FOR CONCRETE AND MASONRY WALLS.

** MAXIMUM ALLOWABLE OPENING WIDTH PROVIDING AN ENGINEER OF RECORD VERIFIED THE SELECTED MOUNTING BOLT WALL ANCHORS OR THREADED INTERFACES ARE STRUCTURALLY CAPABLE OF MEETING THE REQUIRED LOADS.